



TOYOTA

LAND CRUISER 70, 73, 74 SERIES

ARB DELUXE BULL BARS & WINCH BARS

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
All	Winch Bar	Tow Points, Recessed Indicators, Black	9.5XP, M12000, XD9000, M8274, M8000.	3412130

IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Model</u>	<u>Recommended Lighting</u>
All	70 Series	800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
All	3B Diesel, Right Side Mount.	SS73HF

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>	
All Gas & Diesel, SWB & MWB 70 Series models	Front	All models - Light Load to 110lbs	Spring	2.0"	2	CS006FM	
			Shock		2	*N88/N92	
	Installation	Spring Bushing				2	OMESB1
						1	OMEGS2
						1	OMEGP1
				Trim Packer			TP01
				Steering Damper		1	OMESD24
	Front	Heavy Load 110 to 240lbs	Spring	2.0"	2	CS006F	
			Shock		2	N88	
	Installation	Spring Bushing				2	OMESB1
			U Bolt		4	OMEU51	
			Greasable Shackle		1	OMEGS2	
					1	OMEGP1	
			Trim Packer			TP01	
Rear	Medium Load to GVW	Spring	2.75"	2	CS017RA/B		
		Shock		2	N85		
Installation	Spring Bushing				2	OMESB1	
			U Bolt		4	OMEU59A	
			Greasable Shackle		1	OMEGS2	
					1	GSP01	
			Constant 440lb Load to GVW	Spring	2.75"	2	CS004RA/B ²
Rear	Constant 440lb Load to GVW	Shock		2	N85		
Installation	Spring Bushing				2	OMESB1	
			U Bolt		4	OMEU59A	
			Greasable Shackle		1	OMEGS2	
					1	GSP01	
			Anti Inversion Kit**		1	FK08	

¹ CS006FM is a modified CS006F spring (4th leaf from top of spring stack removed.) Use where bump stop heights exceed 3.93".

² If bump stop measurement exceeds 59-63" remove third leaf from top of spring stack to prevent shock absorber from topping out.

** Anti Inversion Kit FK08 is required for installation if Greasable shackles are not installed.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
To 1989	Front	12 Bolt	33 (1.31")	30	ALL	RD33
	Rear	12 Bolt, Semi Float	33 (1.31")	30	ALL	RD124
