



# TOYOTA

## ARB DELUXE BULL BARS & WINCH BARS

### Including Air Bag Equipped Models

Year	Type	Features	Winches	Part No.
1995-04	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	9.5xp, HS9500, XD9000, M8000	3423020
2005-08	Winch Bar	Airbag Approved, Recessed Indicators, Urethane Buffers, Tow Points, Black	9.5xp, HS9500, XD9000, M8000	3423030

## IPF LIGHTS & LIGHTING ACCESSORIES

Year	Part No.	Recommended Lighting
1995-04	3423020	800XSD, 900XS, 900HID, 960S/R, 868CS, 968CS, J-01
2005-08	3423030	800XSD, 900XS, 900HID, 960S/R, 868CS, 968CS, J-01

## SAFARI SNORKELS

Year	Recommended Snorkel	Part No.
1995-04	Toyota Tacoma V6 Snorkel	SS170HF
2005-08	Not Available	N/A

Refer to [www.safari4x4.com.au](http://www.safari4x4.com.au) for details.

## OLD MAN EMU SUSPENSION PRODUCTS

Year/Model	Location	Description	Type	Lift	Quantity	Part No.
1998-04	Front	Stock/Light Load (0-110lbs)	Spring	1.75"	2	OME880 <sup>1</sup>
			Shock		2	N91SC
		Heavy Load (110-220lbs)	Spring	1.75"	2	OME881 <sup>1</sup>
			Shock		2	N91S
	Rear	Medium Load	Spring	2.25"	2	CS046RA/B <sup>2</sup>
			Shock		2	*N85/N94
1998-04	Installation	Rear Leaf Spring Bushing Kit			2	OMESB89 <sup>3</sup>
		Exhaust Bracket			1	FK21 <sup>4</sup>
	Optional	Front Trim Spacer 5mm			1	OME95PF5
		Rear Greasable Shackle Kit			1	OMEGS12 <sup>3</sup>
	Rear Greasable Bushing Kit			2	OMESB88 <sup>3</sup>	

<sup>1</sup> OME front coils can only be installed with OME Nitrocharger struts and coil seats.

<sup>2</sup> For Light Load applications, the 2nd leaf from the bottom of the spring pack can be removed for improved ride comfort. CS046RA/B rear Leaf Springs only fit post 1998 Xtra Cab and Double Cab models.

<sup>3</sup> OMESB89 must be used with original shackles. OMESB88 must be used with OMEGS12 greasable shackles. OE rubber bushings are used at fixed end of spring. Install original OE bushings from OE springs if they are in good condition, or source new OE bushings from dealership.

<sup>4</sup> FK21 Exhaust Bracket is a mandatory fitment to ensure exhaust system clears springs.

\*Firmer shock

### OLD MAN EMU SUSPENSION PRODUCTS

<u>Year/Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
2005-08	Front	Stock/Light Load (0-110lbs)	Spring	1.75"	2	OME885
			Shock		2	N140S
		Heavy Load (110-220lbs)	Spring	1.75"	2	OME886
			Shock		2	N140S
2005-08	Rear	Medium Load (0lbs to GVW)	Spring	2.75"	2	CS047R <sup>1</sup>
			Shock		2	N182
	Installation	Fitting Kit			1	FK29 <sup>3</sup>
		U Bolts			4	OMEU53A
	Optional	Extra Leaf			1	D29XL <sup>2</sup>
Rear Spring Bushing Kit					OE <sup>2</sup>	

OME front coils can only be installed with OME Nitrocharger struts and coil seats.

<sup>1</sup> **IMPORTANT NOTE: Leaf spring bushes must be OE. Use Toyota part number 90389-A0003 (quantity of 8 total)**

<sup>2</sup> Add XL to raise spring 15mm and increase rate. Removed leaf 3 to lower spring 15mm and reduce rate

<sup>3</sup> Driveshaft packer kit is designed to space down carrier bearing to reduce tailshaft flange angle, thereby reducing driveline vibration.

### ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
1996-04	Front	7.5" dia. RG, 10 bolt, IFS	28 (1.1")	27	ALL	RD90
2005-08	Front	8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.91 & UP	RD111
		8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.73 & DN	RD121
1996-08	Rear	8" dia. RG, 12 bolt	33 (1.31")	30	ALL	RD129

**\*\*These lockers suit open differentials only, and will not replace the factory e-locker unless the housing and 3rd member are replaced with open end diffs.**