## ARB

## **MITSUBISHI**

## MONTERO SPORT / CHALLENGER

ARB DELUXE BULL BARS & WINCH BARS

**Including Air Bag Equipped Models** 

YearTypeFeaturesWinchesPart No.1997-99Winch BarSport - Airbag Approved, Recessed Indicators,XD9000, M8000,3435010

Urethane Buffers, Tow Points, Black M6000

**IPF LIGHTS & LIGHTING ACCESSORIES** 

Year Type Recommended Lighting

1997-99 Winch Bar 800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01, 630RV

SAFARI SNORKELS

 Year
 Recommended Snorkel
 Part No.

 N/A
 N/A

OLD MAN EMU SUSPENSION PRODUCTS									
Model	Location	<u>Description</u>	<u>Type</u>	<u>Lift</u>	Quantity	Part No.			
2000-04	Front	Coil Spring - Stock/Light Load	Spring			303011 <sup>1</sup>			
			Shock		2	N57G			
2000-04	Rear	Coil Spring - Medium Load (0lbs to GVW)	Spring	1.50"	2	OME911			
			Shock		2	N116			
2000-04	Rear	Coil Spring - Heavy Constant	Spring	1.50"	2	OME910			
			Shock		2	N116			
1998-99	Front	Rear Leaf Spring - Stock/Light Load	Spring		2	303011 <sup>1</sup>			
			Shock		2	N57G			
1998-99	Rear	Rear Leaf Spring - Medium Load	Spring	1.0"	2	CS040R <sup>2</sup>			
			Shock		2	N56/N54			
1998-99	Rear	Rear Leaf Spring - Heavy Constant (440lbs to GVW)	Spring	1.0"	2	CS041R <sup>2</sup>			
			Shock		2	N56			
1998-99	Installation	Rear Leaf Spring - Leaf Spring Bushing Kit			2	OMESB83 <sup>2</sup>			
	Optional	Rear Extra Leaf	•			D7XL <sup>3</sup>			

Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upperbump stop clearance and 2/3 lower bump stop clearance.

<sup>&</sup>lt;sup>3</sup> Extra Leaf can be fitted for heavier constant load carrying ability.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES											
<u>Year</u>	<u>Axle</u>	<u>Description</u>	Shaft	<u>Spline</u>	Ratio	Part No.					
ALL	Front	IFS, 28 Spline	28.8 (1.13")	28	ALL	RD110					
ALL	Rear	3.0L, 9.00" RG	30.5 (1.20")	28	ALL	RD46					
ALL	Rear	3.5L, 9.50" RG	35.5 (1.40")	31	ALL	N/A					

<sup>&</sup>lt;sup>2</sup> CS040R & CS041R springs can only be installed with OMESB83 bushings.